



- Dispositivo fermo macchina (total-stop) con disinserimento motore ritardato
- Pompa acqua a tre pistoni in ceramica con testata in ottone o nichel
- Motore elettrico a quattro poli servizio continuo con dispositivo salva-motore
- Accoppiamento motore-pompa con giunto elastico (eccetto 120/10 e 150/15)
- Valvola (by-pass) di regolazione pressione acqua
- Valvola di regolazione con tubo di erogazione detergente in bassa pressione
- Manometro
- Interruttore accensione/spegnimento con spia luminosa
- Cavo allacciamento elettrico con spina (3,5 m)

- Delayed total stop control
- Water pump with three ceramic pistons and brass or nickel head
- Continuous service four poles electric motor with thermal protection
- Motor-pump connection with flexible coupling (except 120/10 and 150/15)
- By-pass valve with water pressure adjustment
- Regulation valve with injection hose of chemical products in low pressure
- Manometer
- On/Off switch with warning light
- Power cord with plug (3,5 m)



IDROPULITRICI PROFESSIONALI AD ACQUA FREDDA

PROFESSIONAL COLD WATER HIGH PRESSURE CLEANERS

MODELLO - MODEL		120/10	150/15	150/21	200/15	200/21	200/30
CODICE - CODE		01PF25	01PF26	01PF27	01PF28	01PF29	01PF30
PRESSIONE ACQUA MAX - WATER PRESSURE MAX	bar	120	150	150	200	200	200
	psi	1.740	2.175	2.175	2.900	2.900	2.900
PORTATA ACQUA - FLOW RATE	l/h	600	900	1.260	900	1.260	1.800
	l/min	10	15	21	15	21	30
TEMP. MAX ALIMENTAZIONE - MAX INLET TEMPERATURE	°C	40	40	40	40	40	40
POTENZA MOTORE POMPA - PUMP POWER	kW	2,2	4,0	5,5	5,5	7,4	11,2
	HP	3	5,5	7,5	7,5	10	15
VELOCITÀ - SPEED	rpm	1.450	1.450	1.450	1.450	1.450	1.450
ALIMENTAZIONE ELETTRICA - POWER SUPPLY	V, ~, Hz	230, 1, 50	230/400, 3, 50	230/400, 3, 50	230/400, 3, 50	230/400, 3, 50	400, 3, 50
PREZZO - PRICE	Euro						



Accessori a richiesta, Accessories on request:

Avvolgitubo manuale per tubo alta pressione l max = 20 m
Manual hose reel for high pressure hose 20 m long max

cod.	mod.	Euro
01AC248	20 m	



Accessori in dotazione, Equipment:

- Gomma alta pressione l = 10 m con attacco rapido a vite
High pressure hose 10 m long with quick screw connection
- Semilancia atermica con attacco rapido a vite
Athermic semilance with quick screw connection
- Impugnatura per comando a distanza
Spray gun for remote control
- Prolunga mobile l = 70 cm con testina pressione regolabile (per erogazione detergente in bassa pressione) ed ugello (eccetto 200/30)
Removable lance 70 cm long with adjustable pressure brass head (for the low pressure injection of chemical products) and nozzle (except 200/30)
- Lancia doppia l = 60 cm con erogazione detergente in bassa pressione mediante manopola (solo 200/30)
Double lance 60 cm long with low pressure injection of chemical products through handle (200/30 only)